



## Original Koyo Bearing LTD



VAK 25 Bearing 2D drawings and 3D CAD models

0.984 Inch | 25 Millimeter x 1.22 Inch | 31  
Millimeter x 1.311 Inch | 33.3 Millimeter TIMKEN  
VAK 25 Pillow Block Bearings

Bearing No. VAK 25

Category	Pillow Block Bearings
Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	2.511
EAN	0087796057128
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Eccentric Collar
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	10 Millimeter
Relubricatable	Yes
Insert Part Number	GRAE25RRB
Seals	Double Land Riding Rubber Contact
Housing Configuration	1 Piece Solid
Inch - Metric	Metric
Other Features	Single Row   Spherical   Normal Duty   Low Base   With Set Screw
Long Description	2 Bolt Pillow Block; 25MM Bore; 33.3MM Base to Center Height; Eccentric



## Original Koyo Bearing LTD

	Collar Mount; Ball Bearing; Relubricatable; Cast Iron; Double Land Riding Rubber Contact; Non- expansion
Category	Pillow Block
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer URL	<a href="http://www.timken.com">http://www.timken.com</a>
Manufacturer Item Number	VAK 25
Weight / LBS	1.67
d	0.984 Inch   25 Millimeter
Bolt Spacing Maximum	0 Inch   0Millimeter
Bolt Spacing Minimum	0 Inch   0Millimeter
B	1.311 Inch   33.3 Millimeter
D	1.22 Inch   31 Millimeter
Nominal Bolt Center to Center	4.1 Inch   105 Millimeter
Actual Bolt Center to Center	4.1 Inch   105Millimeter
Shaft Size d	0.984 in
Bearing Type	Ball Bearing
Inside Ring Outside Diameter	0.531 in
Dimension T	0.705 in
Series	Standard
Weight	1.671 lb
Seal Type	Molded Shroud
Base to Center Height H	33.34 mm
Total Length L	139.70 mm
Total Width A	1.406 in
Bolt Hole Spacing J	104.8 mm



## Original Koyo Bearing LTD

Bolt Hole Width N	11.1 mm
Bolt Hole Length N1	20.6 mm
Foot Height H1	11.9 mm
Total Height H2	68.3 mm
Dimension L1	46.6 mm
Inside Ring Width B	=Bearings1_Inside Ring Width= mm
Center of Bearing from End S	7.6 mm
Dimension B1	1.220 in
Static Load Rating	1750 lbf
Dynamic Load Rating	3490 lbf